

RECEIVED  
CENTRAL FAX CENTER

JUN 20 2006

**IN THE CLAIMS:****Listing of Claims:**

- 1 1. (previously presented) A punch assembly, comprising:  
2 a mandrel, comprising an elongate shaft having a distal end and a disk-shaped  
3 head opposite said distal end, said head defining an outer diameter, and a substantially  
4 flat face defined by a threaded bore formed therein, said shaft defining a generally  
5 constant diameter over its entire length;  
6 a punch defining a generally cylindrical shape, and having circular cross-section  
7 along a longitudinal axis, a base end and a cutting end, said cutting end defining a cutting  
8 edge terminating in at least one pointed tip, said base end defining a substantially flat face  
9 having an aperture formed therethrough; and  
10 attachment means for attaching said punch to said mandrel whereby said base end  
11 is in adjacent to said face and said attachment means comprising a bolt extending through  
12 said aperture and threadedly engaging said threaded bore..
- 1 2. (previously presented) The assembly of Claim 1, wherein said punch further  
2 comprises a generally cylindrical cross-section defining an outer diameter, said head  
3 outer diameter being greater than said punch outer diameter.
- 1 3. (original) The assembly of Claim 2, wherein said punch further defines a pair of  
2 opposing arcuate portions on said cutting surface in spaced relation.
- 1 4. (currently amended) The assembly of Claim 3, wherein said punch comprises a pair  
2 of said tips, said tips and said arcuate portions in alternating spaced relation with each  
3 other.
- 1 5. (canceled)

1 6. (currently amended) The assembly of Claim 4, wherein said mandrel comprises a  
2 elongated shaft having a solid cross-section and defining a distal end and a head end, said  
3 head extending from said head end.

1 7. (original) The assembly of Claim 6, wherein said head defines a generally circular  
2 cross-section and said threaded bore is located at the center of said cross-section.

1 8. (original) The assembly of Claim 7, wherein said punch defines a cross-section  
2 having a generally circular ring shape.

1 9. (currently amended) A method for creating holes in sheets of material, comprising  
2 the steps of:

3 obtaining a powder-actuated tool comprising a receiver;

4 attaching a punch assembly to said receiver, said punch assembly comprising:

5 a mandrel, comprising a shaft and a head, said head defining an outer  
6 diameter and a face;

7 a punch defining a base end and a cutting end, said cutting end defining a  
8 cutting edge terminating in at least one tip; and

9 attachment means for attaching said punch to said mandrel;

10 placing at least one said punch tip against said sheet; and

11 activating said powder-actuated tool to drive said punch in a direction that is away  
12 from said receiver, through said sheet thereby forming a said hole, said activating  
13 excluding said punch from rotating.

1 10. (original) The method of Claim 9, wherein said attaching, placing and activating  
2 steps comprises attaching, placing and activating using a punch further defining a pair of  
3 opposing arcuate portions on said cutting surface in spaced relation.

1 11. (original) The method of Claim 10, wherein said attaching, placing and activating  
2 steps comprises attaching, placing and activating using a punch further defining a pair of  
3 said tips, said tips and said arcuate portions in alternating space relation with each other.

1 12. (original) The method of Claim 11, wherein said attaching, placing and activating  
2 steps comprise attaching, placing and activating using a punch assembly further defined  
3 by:

4 said mandrel further defining a threaded bore formed in said face;

5 said punch further defines a bore formed in said base end; and

6 said attachment means comprises at least one bolt inserted through said punch  
7 bore and threadedly engaging said threaded bore.

1 13. (original) The method of Claim 12, wherein said attaching, placing and activating  
2 steps comprise attaching, placing and activating using a mandrel defined by a diameter  
3 that is greater than a diameter defined by said punch;

4 whereby said diameter of said mandrel prevents said punch assembly from  
5 passing through said hole.

1 14. (previously presented) A punch assembly for punching a hole in a section of metal  
2 sheet, comprising:

3 a mandrel, comprising an elongate shaft and a head, said head defining an circular  
4 outer diameter and a generally flat face;

5 a punch defining a generally hollow cylindrical shape terminating in a closed  
6 base end and an open cutting end, said cutting end defining a cutting edge at an outer  
7 periphery of said cutting end defining a pair of pointed tips having curved edges, said  
8 curved edges adjacent to curved trough sections, said base end defining a generally flat  
9 surface; and

10 attachment means for attaching said punch to said mandrel whereby said base end  
11 is mated to said mandrel face.

1 15. (original) The assembly of Claim 14, wherein:

2 said mandrel further defines a threaded bore formed in said face;

3 said punch further defines a bore formed in said base end; and

4 said attachment means comprises at least one bolt inserted through said punch  
5 bore and threadedly engaging said threaded bore.

1 16. (previously presented) The assembly of Claim 14, wherein said mandrel comprises  
2 an elongated shaft defining a distal end and a head end, said head extending from said  
3 head end.

1 17. (original) The assembly of Claim 14, wherein said punch defines a cross-section  
2 having a generally circular ring shape.

1 18. (previously presented) The assembly of Claim 14, wherein said punch further  
2 comprises a generally cylindrical cross-section defining an outer diameter, said head  
3 outer diameter being greater than said punch outer diameter.

1 19. (original) The assembly of Claim 14, wherein said punch further defines a pair of  
2 opposing arcuate portions on said cutting surface in spaced relation.

1 20. (previously presented) The assembly of Claim 19, wherein said punch comprises a  
2 pair of said tips, said tips and said arcuate portions in alternating space relation with each  
3 other.